



www.perma-cool.com


**Installation
Instructions**
This guide covers the following:

14845

Chevrolet Oil Filter Bypass Relief Valve Plug

IMPORTANT! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION.

This part is designed to plug factory pressure relief valve in GM V8 engines. The oil filter support base does not need to be removed for installation. The valve and spring will move, allowing the installation of the teflon plug. This plug is designed to be installed only once. Removal will break the holding ridges.



For additional accessories or replacement parts
visit www.perma-cool.com



www.perma-cool.com


**Installation
Instructions**
This guide covers the following:

14845

Chevrolet Oil Filter Bypass Relief Valve Plug

IMPORTANT! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION.

This part is designed to plug factory pressure relief valve in GM V8 engines. The oil filter support base does not need to be removed for installation. The valve and spring will move, allowing the installation of the teflon plug. This plug is designed to be installed only once. Removal will break the holding ridges.



For additional accessories or replacement parts
visit www.perma-cool.com



www.perma-cool.com


**Installation
Instructions**
This guide covers the following:

14845

Chevrolet Oil Filter Bypass Relief Valve Plug

IMPORTANT! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION.

This part is designed to plug factory pressure relief valve in GM V8 engines. The oil filter support base does not need to be removed for installation. The valve and spring will move, allowing the installation of the teflon plug. This plug is designed to be installed only once. Removal will break the holding ridges.



For additional accessories or replacement parts
visit www.perma-cool.com



www.perma-cool.com


**Installation
Instructions**
This guide covers the following:

14845

Chevrolet Oil Filter Bypass Relief Valve Plug

IMPORTANT! READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION.

This part is designed to plug factory pressure relief valve in GM V8 engines. The oil filter support base does not need to be removed for installation. The valve and spring will move, allowing the installation of the teflon plug. This plug is designed to be installed only once. Removal will break the holding ridges.



For additional accessories or replacement parts
visit www.perma-cool.com